

FORESTRY MULCHERS FOR SKID STEERS

DML/SSL - DML/SSL/VT

Forestry mulcher with fixed tooth rotor for excavators.



40-70 hp



Ø 5 in max



STANDARD EQUIPMENT

17/34cc variable manual displacement hydraulic piston motor with relief and anticavitation valve (12-28 gpm) (DML/SSL)	Hydraulic hoses
55/38cc variable torque hydraulic piston motor (16-30 gpm) (DML/SSL/VT)	Hydraulic front hood
Diverter valve (plug in and play)	Working pressure control gauge
Safety and anticavitation valve	Pushing frame
Enclosed / anti dust machine body	Protection chains
Motor enclosed in the frame	Welded counterblades
Belt transmission	

OPTIONS

32/65cc variable manual displacement hydraulic piston motor with relief and anticavitation valve (DML/SSL)	Multiple tooth options
Customized setting hydraulic motor	
Case drain required	

MODEL	DML/SSL 125	DML/SSL 150	DML/SSL 175	DML/SSL/VT 125*	DML/SSL/VT 150*	DML/SSL/VT 175*
Engine (hp)	40-70	40-70	40-70	40-70	40-70	40-70
Flow rate (gal/min)	12-28	12-28	12-28	16-30	16-30	16-30
Pressure (PSI)	2600-3600	2600-3600	2600-3600	2600-5080	2600-5080	2600-5080
Working width (in)	49	58	68	49	58	68
Total width (in)	60	69	79	60	69	79
Weight (lbs)	1510	1731	1951	1510	1731	1951
Rotor diameter (in)	11.8	11.8	11.8	11.8	11.8	11.8
Max shredding diameter (in)	5	5	5	5	5	5
No. blades type E	30	36	42	30	36	42

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.

*Variable displacement hydraulic motor.

*Reflects two motor options.



Blade E
(standard)

Blade E/HD
(option)