

MULTITASKS

SFL

Stone crusher and forestry mulcher for PTO tractors with fixed teeth rotor.



120-160 hp



Ø 6 in max



Depth 6 in

STANDARD EQUIPMENT

Hydraulic rear hood	Poly-Chain® belts transmission
Inner anti wear clad plates FCP	Gearbox with freewheel
Enclosed machine body	PTO shaft with cam clutch
Hydraulic hoses integrated in the frame	Bolted-on rotor shafts (in forged steel)
Cylinder protection	Welded steel counter-blades
Inside lateral protection	Adjustable Hardox® counter-blade
Dual row protection chains	

OPTIONS

Hydraulic top link	Dozing blade
Mechanical guard frame	Grader blade (road kit)
Hydraulic guard frame	Hydraulic support roller
IVT - CVT or creeper transmission strongly recommended	Forestry tires and carrier belly pan strongly recommended

MODEL	SFL 150	SFL 175	SFL 200
Engine (hp)	120-160	120-160	120-160
PTO (rpm)	540-1000	540-1000	540-1000
Working width (in)	63	72	81
Total width (in)	75	84	94
Weight (lbs)	3197	3527	3858
Rotor diameter (in)	17.7	17.7	17.7
Max shredding diameter (in)	6	6	6
Max working depth (in)	6	6	6
No. teeth type STCL/3+C/3/SS	30+4	34+4	40+4

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.



STC/3
(standard)



C/3/SS
(side scraper)