

## MULTITASKS

# SFH - SFH/HP

Stone crusher, forestry tiller and mulcher for PTO tractors with fixed teeth rotor.



300-500 hp



Ø 14 in max (Stones)  
Ø 18 in max (Trees)  
Ø 22 in max (Stump)



Depth 16 in

### STANDARD EQUIPMENT

Hydraulic rear hood	Gearbox with freewheel
Inner anti wear clad plates FCP	Gearbox with oil cooling system (SFH/HP)
Adjustable extended 3 point linkage	PTO shaft
Enclosed machine body	Friction clutches
Centralized greasing hub	Bolted-on rotor shafts (in forged steel)
Hydraulic hoses integrated in the frame	Hydraulic top link
Cylinder protection	Z style self ranging system of the PTO drive shaft/gearbox
Inside lateral protection	Forged and hardened interchangeable counter-blades
Bolted on protection chains	Third row of interchangeable forged and hardened counter-blades
Transmission with side gearbox	Adjustable Hardox® counter-blade
Side gearbox with oil cooling system	

### OPTIONS

Bolted grid on rear hood	Hydraulically adjustable skids
High Speed Transmission	Hydraulic support roller
W style self aligning device between PTO drive shaft/gearbox	
IVT - CVT or creeper transmission strongly recommended	Forestry tires and carrier belly pan strongly recommended

MODEL	SFH 225	SFH 250	SFH/HP 225	SFH/HP 250
<b>Engine</b> (hp)	300-400	300-400	360-500	360-500
<b>PTO</b> (rpm)	1000	1000	1000	1000
<b>Working width</b> (in)	91	101	91	101
<b>Total width</b> (in)	107	116	107	116
<b>Weight</b> (lbs)	13691	14330	13691	14330
<b>Rotor diameter</b> (in)	35.4	35.4	35.4	35.4
<b>Max shredding diameter</b>	Stones (in)	14	14	14
	Trees (in)	18	18	18
	Stump (in)	22	22	22
<b>Max working depth</b> (in)	16	16	16	16
<b>No. teeth</b> type G/3+STC/FP	62+8	68+8	62+8	68+8

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.



**G/3**  
(standard)



**G/3/HD**  
(option)



**STC/FP**  
(side scraper)