

FORESTRY MULCHERS FOR SKID STEERS

PMM/SSL

Brush mulcher with hammer/flail rotor for skid steers.



60-100 hp



Ø 3 in max



STANDARD EQUIPMENT

32/65cc variable manual displacement hydraulic piston motor with relief and anticavitation valve

Self levelling protection flaps

Motor enclosed in the frame

Supporting service leg

Belt transmission

Welded counterblades

Hydraulic hoses

Self cleaning rear roller with integrated skids

Front hood with mechanical adjustment

Attachment plate with self levelling device

Adjustable skids

OPTIONS

Customized setting hydraulic motor

Stronger bearing for roller

Possibility to have the rotor equipped with PML hammers or Y-flails

Case drain required

MODEL	PMM/SSL 150	PMM/SSL 175	PMM/SSL 200
Engine (hp)	60-100	65-100	70-100
Flow rate (gal/min)	15-33	15-33	15-33
Pressure (PSI)	2600-3600	2600-3600	2600-3600
Working width (in)	61	70	80
Total width (in)	69	79	86
Weight (lbs)	1742	1874	2006
Rotor diameter (in)	17.3	17.3	17.3
Max shredding diameter (in)	3	3	3
No. hammers type PMM	18	22	24
No. flails type Y/3	18	22	24

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.



Hammer PMM
(standard)



Flail Y/3
(option)