

FORESTRY MULCHERS FOR EXCAVATORS

UML/HY - UML/HY/VT



24-45 gal/min



Ø 6 in max



7-15 t

STANDARD EQUIPMENT

80/50cc variable torque hydraulic piston motor (26-38 gpm) (UML/HY/VT)	Belt transmission (UML/HY)
32/65cc variable manual displacement hydraulic piston motor with relief and anticavitation valve (24-45 gpm) (UML/HY)	Poly Chain Belt Transmission (UML/HY/VT)
Flow control system valve	Bulkhead for hydraulic connections
Safety and anticavitation valve	Hydraulic front hood
Enclosed / anti dust machine body	Dual row protection chains
Motor enclosed in the frame	Welded counterblades

OPTIONS

Customized setting hydraulic motor	Customized attachment bracket with pins and leg
Diverter valve	Multiple tooth options
Rear hood with mechanical adjustment	Rotor Bite Limiter (UML/HY/VT)
Customized attachment bracket with pins	
Not supplied with hoses	Case drain required

MODEL	UML/HY 100*	UML/HY 125*	UML/HY 150*	UML/HY/VT 100*	UML/HY/VT 125*	UML/HY/VT 150*
Flow rate (gal/min)	24-45	24-45	24-45	26-38	26-38	26-38
Pressure (PSI)	2611-3626	2611-3626	2611-3626	2600-5080	2600-5080	2600-5080
Excavator weight (t)	7-15	7-15	7-15	7-15	7-15	7-15
Working width (in)	43	53	62	43	53	62
Weight (lbs)	1852	1940	2315	1874	1962	2337
Rotor diameter (in)	16.5	16.5	16.5	16.5	16.5	16.5
Max shredding diameter (in)	6	6	6	6	6	6
No. teeth type C/3+C/3/SS	20+2	26+2	32+2	20+2	26+2	32+2
type I+C/3/SS	28+2	36+2	42+2	28+2	36+2	42+2

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.

*Variable displacement hydraulic motor.

ROTOR TYPE C



C/3
(standard)



C/3/HD
(option)



BL Blade
(option)



K/3
(option)

ROTOR TYPE I



I
(option)



C/3/SS
(side scraper)