

**NEW**

FORESTRY MULCHERS FOR EXCAVATORS

# BL4/EX/VT

Forestry mulcher with bite limiter technology.



40-79 gal/min



Ø 12 in max



18-25 t

## STANDARD EQUIPMENT

110/60cc variable torque hydraulic piston motor	Poly Chain Belt Transmission
Flow control system valve	Bulkhead for hydraulic connections
Diverter valve	Hydraulic rear hood
Safety and anticavitation valve	Adjustable skids
Enclosed / anti dust machine body	Rotor Bite Limiter
Motor enclosed in the frame	

## OPTIONS

160/108cc variable torque hydraulic piston motor	Hydraulic thumb
Customized setting hydraulic motor	Spike Pro counter-blade
Hydraulic front hood for excavator AUX line	Customized attachment bracket with pins
Rear deflector	Multiple tooth options
Additional reinforced side plates	Sonic System
Front fixed thumb bracked	
Not supplied with hoses	Case drain required

MODEL	BL4/EX/VT 125	BL4/EX/VT 150
<b>Flow rate</b> (gal/min)	38-79	38-79
<b>Pressure</b> (PSI)	3200-5080	3200-5080
<b>Excavator weight</b> (t)	18-25	18-25
<b>Working width</b> (in)	53	62
<b>Weight</b> (lbs)	3417	3638
<b>Rotor diameter</b> (in)	18.6	18.6
<b>Max shredding diameter</b> (in)	12	12
<b>No. blades</b> type BL+C/3/SS	20+2	24+2

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.

All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.



**BL Blade**  
(standard)



**C/3/SS**  
(side scraper)