

NEW

## STUMP CUTTERS FOR EXCAVATORS

# SCL/HY

Disc stump cutters for excavators.



13-26 gal/min



4-7.5 t

### STANDARD EQUIPMENT

32/65cc variable manual displacement hydraulic piston motor with relief and anticavitation valve

Belt transmission

Flow control system valve

Bulkhead for hydraulic connections

Diverter valve (plug in and play)

Hydraulic front hood

Safety and anticavitation valve

Rear fixed heel

Enclosed / anti dust machine body

Screwed protection chains

Motor enclosed in the frame

### OPTIONS

Customized setting hydraulic motor

Customized attachment bracket with pins and leg

Customized attachment bracket with pins

Not supplied with hoses

Case drain required

### MODEL

### SCL/HY

**Flow rate** (gal/min)

13-26

**Pressure** (PSI)

2600-5080

**Excavator weight** (t)

4-7.5

**Disc diameter** (in)

22

**Total width** (in)

24

**Weight** (lbs)

1014

**Rotor diameter** (in)

22.4

**No. teeth** type L1+L2

15+15

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.



**L1**  
(standard)



**L2**  
(standard)

All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.