

## FORESTRY MULCHERS

# UML/ST

Forestry mulcher for PTO tractors with fixed tooth rotor.



50-110 hp



Ø 8 in max



### STANDARD EQUIPMENT

Hydraulic rear hood	PTO shaft with cam clutch
Dual row protection chains	Bolted-on rotor shafts (in forged steel)
Transmission with belts	Welded steel counter-blades
Gearbox with freewheel	Adjustable skids
Possibility to choose Transmission 540 / 1000 rpm	

### OPTIONS

Frontal attachment	Hydraulic top link
Extended 3 point linkage	Special skids to go underground
Multiple tooth options	Mechanical guard frame
IVT - CVT or creeper transmission strongly recommended	
Forestry tires and carrier belly pan strongly recommended	

MODEL	UML/ST 125	UML/ST 150	UML/ST 175	UML/ST 200
<b>Engine</b> (hp)	50-100	60-110	70-110	80-110
<b>PTO</b> (rpm)	540 or 1000	540 or 1000	540 or 1000	540 or 1000
<b>Working width</b> (in)	62	62	72	81
<b>Total width</b> (in)	74	74	83	93
<b>Weight</b> (lbs)	2050	2050	2337	2624
<b>Rotor diameter</b> (in)	16.7	16.7	16.7	16.7
<b>Max shredding diameter</b> (in)	8	8	8	8
<b>No. teeth</b> type C/3+C/3/SS	26+2	32+2	36+2	42+2
type I+C/3/SS	36+2	42+2	50+2	58+2

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.

### ROTOR TYPE C



**C/3**  
(standard)



**C/3/HD**  
(option)



**BL Blade**  
(option)



**K/3**  
(option)

### ROTOR TYPE I



**I**  
(option)



**C/3/SS**  
(side scraper)