

FORESTRY MULCHERS

UML/DT

Forestry mulcher for PTO tractors with fixed tooth rotor.



80-130 hp



Ø 10 in max



STANDARD EQUIPMENT

Hydraulic rear hood	Transmission with belts
Enclosed machine body	Gearbox with freewheel
Centralized greasing hub	PTO shaft with cam clutch
Hydraulic hoses integrated in the frame	Bolted-on rotor shafts (in forged steel)
Cylinder protection	Welded steel counter-blades
Dual row protection chains	Adjustable skids

OPTIONS

Frontal attachment	Hydraulic top link
Extended 3 point linkage	Special skids to go underground
Bolt-on chain's protection plates	Mechanical guard frame
Multiple tooth options	Hydraulic guard frame
IVT - CVT or creeper transmission strongly recommended	Forestry tires and carrier belly pan strongly recommended

MODEL	UML/DT 200	UML/DT 225
Engine (hp)	80-130	90-130
PTO (rpm)	1000	1000
Working width (in)	81	92
Total width (in)	91	101
Weight (lbs)	3307	3527
Rotor diameter (in)	16.7	16.7
Max shredding diameter (in)	10	10
No. teeth type C/3+C/3/SS	42+2	46+2
type I+C/3/SS	58+2	66+2

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.

ROTOR TYPE C



C/3
(standard)



C/3/HD
(option)



BL Blade
(option)



K/3
(option)

ROTOR TYPE I



I
(option)



C/3/SS
(side scraper)