

FORESTRY MULCHERS

UMM/DT

Forestry mulcher for PTO tractors with fixed tooth rotor.



160-240 hp



Ø 12 in max



STANDARD EQUIPMENT

Hydraulic rear hood	Gearbox with freewheel
Enclosed machine body	PTO shaft with cam clutch
Centralized greasing hub	Bolted-on rotor shafts (in forged steel)
Hydraulic hoses integrated in the frame	Hydraulic top link
Cylinder protection	Z style self ranging system of the PTO drive shaft/gearbox
Dual row protection chains	Interchangeable bolted on spike PRO counter-blade
Transmission with belts	Adjustable skids

OPTIONS

Bolt-on chain's protection plates	Special skids to go underground
Hydraulic clutch transmission	Mechanical guard frame
Multiple tooth options	Hydraulic guard frame
W style self aligning device between PTO drive shaft/gearbox	Extra ripper for guard frame
IVT - CVT or creeper transmission strongly recommended	Forestry tires and carrier belly pan strongly recommended

MODEL	UMM/DT 200	UMM/DT 225	UMM/DT 250
Engine (hp)	160-240	170-240	180-240
PTO (rpm)	1000	1000	1000
Working width (in)	81	91	100
Total width (in)	97	106	116
Weight (lbs)	4916	5467	5622
Rotor diameter (in)	19.7	19.7	19.7
Max shredding diameter (in)	12	12	12
No. teeth type C/3+C/3/SS	42+2	46+2	52+2
type I+C/3/SS	58+2	66+2	74+2

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.

ROTOR TYPE C



C/3
(standard)



C/3/HD
(option)



BL Blade
(option)



K/3
(option)

ROTOR TYPE I



I
(option)



C/3/SS
(side scraper)