

## FORESTRY MULCHERS

# UMH/MEGA

Forestry mulcher for PTO tractors with fixed tooth rotor.



350-500 hp



Ø 20 in max



Depth 10 in

### STANDARD EQUIPMENT

Hydraulic rear hood	Hydraulic clutch transmission
Inner anti wear clad plates FCP	Gearbox with freewheel
Adjustable extended 3 point linkage	Gearbox with oil cooling system
Enclosed machine body	PTO shaft
Centralized greasing hub	Bolted-on rotor shafts (in forged steel)
Hydraulic hoses integrated in the frame	Hydraulic top link
Cylinder protection	Z style self ranging system of the PTO drive shaft/gearbox
Inside lateral protection	Forged and hardened interchangeable counter-blades
Dual row protection chains	Third row of interchangeable forged and hardened counter-blades
Poly-Chain® belts transmission	

### OPTIONS

Multiple tooth options	Mechanical guard frame
W style self aligning device between PTO drive shaft/gearbox	Hydraulic guard frame
Hydraulically adjustable skids	Extra ripper for push frame
Special skids to go underground	
IVT - CVT or creeper transmission strongly recommended	Forestry tires and carrier belly pan strongly recommended

MODEL	UMH/MEGA 225	UMH/MEGA 250
<b>Engine</b> (hp)	350-500	350-500
<b>PTO</b> (rpm)	1000	1000
<b>Working width</b> (in)	91	101
<b>Total width</b> (in)	111	120
<b>Weight</b> (lbs)	13162	13933
<b>Rotor diameter</b> (in)	35.8	35.8
<b>Max shredding diameter</b> (in)	20	20
<b>Max working depth</b> (in)	10	10
<b>No. teeth</b> type A/3+MH	58+2	66+2

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.

### ROTOR TYPE A

NEW



**A/3**  
(standard)



**A/3/HD**  
(option)



**MH**  
(side scraper)