

NEW

STONE CRUSHERS

RSM - RSM/HP

Stone crusher for PTO tractors with fixed teeth rotor.



200-360 hp



Ø 20 in max (stones)



Depth 16 in

STANDARD EQUIPMENT

Hydraulic rear hood	Gearbox with freewheel
Interchangeable inner antiwear plates in Hardox®	Friction clutches
Enclosed machine body	PTO shaft with cam clutch
Centralized greasing hub	Bolted-on rotor shafts (in forged steel)
Inside lateral protection	Adjustable Hardox® counter-blade
Protection chains	Penetration skids
Transmission with side gearbox	Side gearboxes with oil cooling system (RSM/HP)

OPTIONS

Bolted grid on rear hood	Dozing blade
Multiple tooth options	Dozing blades with spring system
Hydraulic top link	Side gearbox with oil cooling system (RSM)
IVT - CVT or creeper transmission strongly recommended	Forestry tires and carrier belly pan strongly recommended

MODEL	RSM 200	RSM 225	RSM/HP 200	RSM/HP 225
Engine (hp)	200-300	220-300	300-360	300-360
PTO (rpm)	1000	1000	1000	1000
Working width (in)	82	91	82	91
Total width (in)	98	107	98	107
Weight (lbs)	11155	12103	11155	12103
Rotor diameter (in)	37.0	37.0	37.0	37.0
Max shredding diameter (in)	20	20	20	20
Max working depth (in)	16	16	16	16
No. teeth type G/3+STC/3/FP+STC/FP	94+4+4	106+4+4	94+4+4	106+4+4
type R+R/HD+STC/3/FP+STC/FP	126+20+4+4	144+20+4+4	126+20+4+4	144+20+4+4

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.

ROTOR TYPE G



G/3 (standard)



G/3/HD (option)

ROTOR TYPE R



R 65 (option)



R/HD 65 (option)



STC/3/FP (side scraper)



STC/FP (side scraper)

All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.