

ROCK CUTTERS FOR EXCAVATORS

RC

Rock cutters with fixed teeth for excavators.



5.5-132 gal/min



2-70 t



STANDARD EQUIPMENT

Caged frame with built-in pre-drilled attachment flat plate

Direct drive piston motor with automatic lubrication system that requires no daily maintenance

Hydraulic block with compensating and check valve

Anti-wear plates on drum support

Motor safety cover

Drum with replaceable heavy duty rock teeth

OPTIONS

Custom made attachment plate with pins

Not supplied with hoses

All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.

MODEL	RC 10	RC 15	RC 25	RC 45	RC 65	RC 90	RC 120	RC 220	RC 260	RC 320
Engine (hp)	11-22	20-40	30-50	50-100	65-120	90-140	140-200	200-380	200-400	380-480
Requirements Flow (gal/min)	5.5-10.5	8-16	12-21	17-32	24-40	34-50	45-66	63-90	74-106	92-132
Pressure (PSI)	2600-3600	3300-4400	2200-5080	2600-5080	2600-5080	3200-5080	3500-5080	3500-5500	3600-5500	3600-5500
Excavator weight (t)	1.2-3	2.5-4.5	2.5-7	6-14	9-16	14-22	20-34	28-45	35-55	45-70
Working width (in)	14.5	19	22	25	28	31	33	37	39	49
Weight (lbs)	200	380	661	1036	1411	2513	3230	5313	5952	8047
Rotor diameter (in) (STD)	9	10	15	18	20	23	26	30	30	30
Height without bracket (in)	22	26	30	35	38	49	52	62	66	70
No. teeth	77	69	22+22	26+26	28+28	24+24	24+24	24+24	24+24	28+28

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.



R 65 for RC 90/120 (standard)



R/HD 65 for RC 90/120 (option)



R for RC 25 (option)



R for RC 45/65 (option)



R for RC 220/260/320 (option)